



PROGRAM DATASHEET · NO-UPGRADE FAST CHARGER · EVFC

EVFC060

60 kW Stationary DC EV Fast Charger · Dual Cable

"Two vehicles. One cabinet."



DESCRIPTION

The EVFC060 is an all-in-one, dual-cable DC fast charger that enables up to 60 kW continuous charging output while supporting dynamic power sharing, with highly flexible, field-configurable Vac input power that accepts the most common distribution voltages, reducing overall infrastructure and construction costs.

Industry-standard connectivity supports fast charging, remote services, and software updates on every unit.

Field configuration: patent pending.

FEATURES & BENEFITS

- Highly flexible power input with no de-rating
- Field-replaceable power modules
- Dual-cable setup with power sharing
- Greater than 1 million hours MTBF on PSU topology
- IP54/NEMA 3S enclosure
- Multiple payment/authorization methods: RFID and credit card
- Remote upgrades via over-the-air updates

APPLICATIONS

- Small, mid, and large fleets & depots
- EV infrastructure and service providers
- Public & commercial buildings
- Municipalities
- Retail & hospitality
- Residential & multi-unit dwellings
- OEM test facilities

SPECIFICATIONS

Quoted verbatim from Pii DATA143 (last updated March 3, 2026)

Input voltage	240 Vac Single Phase · 208 or 240 Vac 3-Phase (3P + PE) Delta · 480/277 Vac 3-Phase (3P + N + PE) Wye
Input operating range and current	240 Vac Single Phase: 216 to 252 V, 225 A max, 60 Hz 208/240 Vac 3-Phase Delta: 190 to 252 V, 195 A max, 60 Hz 480 Vac 3-Phase Wye: 432 to 504 V, 85 A max, 60 Hz
Output power	60 kW maximum per charging cable, or 30 / 30 kW power sharing
Output voltage	250 to 920 Vdc
Efficiency	95%
Charging connector	CCS1 and NACS · 5 m cable standard
Charging/data protocols	DIN 70121 and OCPP 1.6J compliant
Network / RFID / display	Cellular 4G LTE, Wi-Fi · ISO/IEC 14443 A/B, ISO 15393, NFC Reader Mode · 7" color LCD
Temperature	Operational -30 °C to +50 °C · Storage -40 °C to +80 °C
Humidity / altitude	Up to 95% non-condensing · 2000 m (6560 ft)
Enclosure / impact	NEMA 3S; IP54 · IK10
Weight	235 kg (charger only)
Dimensions	44.4 x 42.4 x 25.6 in; 63.0 in on pedestal
Mounting	Pedestal sold separately (Part Number: EVQC060-PEDP)
Certifications	cETLus listed to UL 2202, UL 2231-1 & -2, and CSA C22.2 No. 281.1, 281.2 and 346

Will it run on the power your site already has? Get a free Site Check: one utility bill, two photos, one week.
powerinnovations.co/site-check

· Partner program: powerinnovations.co/partners