



PROGRAM DATASHEET · ROLL-UP FAST CHARGER · EVQC-M

EVQC030-M to EVQC060-M

30 - 60 kW Mobile "Shop" DC EV Quick Charger

"The fast charger you don't have to install."



DESCRIPTION

The EVQC030-M to EVQC060-M is a mobile, all-in-one family of DC quick chargers capable of up to 60 kW continuous charging output, with highly flexible, field-configurable Vac input power that accepts the most common distribution voltages. It is directly pluggable into suitable wall outlets.

Industry-standard connectivity supports fast-charging processes and usability on every unit.

Field configuration: patent pending.

FEATURES & BENEFITS

- Highly flexible power input with no de-rating
- Field scalable power, from 30 up to 60 kW
- Greater than 1 million hours MTBF on PSU topology
- IP20/NEMA 1 enclosure
- Field replaceable power modules
- Multiple initiation/authorization methods
- Power derating feature for application flexibility

APPLICATIONS

- Small, mid, and large fleets & depots
- Body shops and repair shops
- Retail and hospitality
- OEM test facilities
- Public and commercial buildings
- Municipalities
- Residential and multi-unit dwellings

SPECIFICATIONS

Quoted verbatim from Pii DATA103 (last updated May 12, 2025)

Input voltage	240 Vac Single Phase · 208 or 240 Vac 3-Phase (3P + PE) Delta · 480/277 Vac 3-Phase (3P + N + PE) Wye
Input operating range and current	240 Vac Single Phase: 216 to 252 V, 225 A max, 60 Hz 208/240 Vac 3-Phase Delta: 190 to 252 V, 195 A max, 60 Hz 480 Vac 3-Phase Wye: 432 to 504 V, 85 A max, 60 Hz
Output power	60 kW maximum
Output voltage	250 to 920 Vdc
Efficiency	95%
Charging connector	CCS1 and NACS · 5 m cable standard
Charging/data protocols	DIN 70121 and OCPP 1.6J compliant
RFID / display	ISO/IEC 14443 A/B, ISO 15393, NFC Reader Mode · 7" color LCD
Temperature	Operational -30 °C to +50 °C · Storage -40 °C to +80 °C
Humidity / altitude	Up to 90% non-condensing · 2000 m (6560 ft)
Enclosure / impact	NEMA 1; IP20 · IK10
Weight	Up to 110 kg (charger only)
Dimensions	36.5 in H (handle) x 33.4 in W x 26.2 in D; body height 20.1 in
Certifications	cETLus listed to UL 2202, UL 2231-1 & -2, and CSA C22.2 No. 281.1, 281.2 and 346

Will it run on the power your site already has? Get a free Site Check: one utility bill, two photos, one week.
powerinnovations.co/site-check · Partner program: powerinnovations.co/partners